



E3/L3 OTR Tire

This non-direction tire is suited for scrapers, dozers and loaders.

FEATURES

- Aggressive and durable lug design
- Non-directional tread design
- Tough, durable casing
- Wide base construction

BENEFITS

- Premium performance in harsh underfoot conditions
- Good fore and aft traction
- Long wearing tread, advanced cut resistance and sidewalls resistant to ozone cracking
- High flotation, improved stability and reduced ground pressure

Specifications: TN

Pattern	Size	PR	TD	OD	SW	Rim	Max Load		Pressure	
				MM	MM		10KM/H S	50KM/H D	10KM/H S	50KM/H D
				(±1%)	(±4%)		Kg	Kg	Kpa	Kpa
(TL) E3/L3	15.5-25	-12	25	1275	395	12	5600	3250	400	250
		-16					6800	3750	550	300
	17.5-25	-12	24	1350	445	14	6150	3650	350	225
		-16					7300	4250	475	300
	20.5-25	-16	27	1490	520	17	8250	5450	350	275
		-20					9500	6000	450	325
	23.5-25	-16	30	1615	595	19.5	8000	6150	300	225
		-20					10900	7300	375	300
		-24					12500	8000	475	350
	26.5-25	-20	35	1750	675	22	13200	8250	350	250
		-24					14000	9250	400	300
		-28					15500	10000	475	350
	29.5-25	-22	38	1875	750	25	15000	10000	325	250
		-28					17500	11500	425	325