



G2/L2 OTR Tire

This directional tire is suited for graders, dozers and loaders.

Features

- Precision angled bars
- Open shoulder grooves
- Tough, durable casing

Benefits

- Maximum traction in soft soil
- Excellent traction for less slippage and superior self-cleaning tread design
- Long wearing tread, advanced cut resistance and sidewalls resistant to ozone cracking

Specifications: TN

Pattern	Size	PR	TD	OD	SW	Rim	Max Load		Pressure	
				MM	MM		10KM/H S	50KM/H D	10KM/H S	50KM/H D
				(±1%)	(±4%)		Kg	Kg	Kpa	Kpa
(TL) G2/L2	1300-24	-12	24.5	1280	330	8.00TG	5600		450	
	1400-24	-12	24	1350	360	8.00TG	6300		425	
	15.5-25	-16	25	1275	395	12	5600	3250	400	250
	17.5-25	-16	26	1350	445	14	6150	3650	350	225
	20.5-25	-16	29	1490	520	17	8250	5450	350	275
		-20					9500	6000	450	325
	10-16.5	-8	18	773	264	8.25	2900		420	
		-10					3130		530	
		-12					3400		630	
	12-16.5	-10					3770		530	
		-12					4045		630	
	10-16.5-8	Normal	12.5	773	264	8.25	1880		415	
		Strengthen					2135		520	
	12-16.5-10	Normal	18	831	307	9.75	3550		350	
		Strengthen					3800		450	
14-17.5	-10	19	920	349	10.5	3105		380		
15-19.5	-12	20	1019	389	11.75	4170		410		
10.5/80-18	-12	21	885	274	9	1935		370		
12.5/80-18	-12	24	985	308	9	2625		370		